

# OVEN Oven group

## Chef220/220/200/2908

### -400V3~

**MG3751991MK**

Oven group with two Chef 220 ovens and a Chef 200 proving cabinet mounted on the stand Chef 2908.

#### CHEF 220 ROASTING BAKING OVEN

- stainless steel cooking cabinet and exterior surface, a large double-glazed door
- temperature: +50-300°C
- separate regulating for upper and lower heating elements
- manual valve for taking out the humidity from the cabinet
- 2 removable pairs of rails

#### CHEF 200 PROVING CABINET

- cabinet, door and external surface stainless steel
- temperature: +20-60°C
- timer 0-120 min or continuous
- pre-heating time (35°C): 20 min
- humidity % can be adjusted
- water pool filling by turning switch
- Optional extras:
  - rack for baking trays: 5 pairs of rails, 450x600 mm



## OVEN Oven group Chef220/220/200/2908 -400V3~

|                               |                          |
|-------------------------------|--------------------------|
| Product capacity              | 2xuuni 1xGN2/1 + 4xGN2/1 |
| Item width mm                 | 800                      |
| Item depth mm                 | 800                      |
| Item height mm                | 1640                     |
| Package volume                | 1.625                    |
| Unit of volume                | m3                       |
| Package volume                | 1.625 m3                 |
| Package length                | 90                       |
| Package width                 | 95                       |
| Package height                | 190                      |
| Package unit of dimension     | cm                       |
| Package dimensions (LxWxH)    | 90x95x190 cm             |
| Net weight                    | 175                      |
| Net weight                    | 175 kg                   |
| Gross weight                  | 195                      |
| Package weight                | 195 kg                   |
| Unit of weight                | kg                       |
| Connection power kW           | 10.3                     |
| Fuse Size A                   | 25                       |
| Connection voltage V          | 400                      |
| Number of phases              | 3PE                      |
| Frequency Hz                  | 50/60                    |
| Startup current A             | 20.3                     |
| Protection rating (IP)        | X4                       |
| Type of electrical connection | Semifixed                |
| Cold water diam.              | 3/4"                     |