

## Oven group

### Chef220/220/220/2908

### -400V3~

**MG3751992MK**

Oven group with 3 Chef 220 roasting-baking ovens and stand Chef 2908.

#### CHEF 220 ROASTING BAKING OVEN

- stainless steel cooking cabinet and exterior surface, a large double-glazed door
- temperature: +50-300°C
- separate regulating for upper and lower heating elements
- manual valve for taking out the humidity from the cabinet
- 2 removable pairs of rails



## Oven group Chef220/220/220/2908 -400V3~

|                               |                               |
|-------------------------------|-------------------------------|
| Product capacity              | 3 x oven à 1xGN2/1 or 2xGN1/1 |
| Item width mm                 | 800                           |
| Item depth mm                 | 800                           |
| Item height mm                | 1640                          |
| Package volume                | 1.625                         |
| Unit of volume                | m3                            |
| Package volume                | 1.625 m3                      |
| Package length                | 90                            |
| Package width                 | 95                            |
| Package height                | 190                           |
| Package unit of dimension     | cm                            |
| Package dimensions (LxWxH)    | 90x95x190 cm                  |
| Net weight                    | 175                           |
| Net weight                    | 175 kg                        |
| Gross weight                  | 195                           |
| Package weight                | 195 kg                        |
| Unit of weight                | kg                            |
| Connection power kW           | 14.1                          |
| Fuse Size A                   | 32                            |
| Connection voltage V          | 400                           |
| Number of phases              | 3PE                           |
| Frequency Hz                  | 50/60                         |
| Startup current A             | 20                            |
| Protection rating (IP)        | X4                            |
| Type of electrical connection | Semifixed                     |