

# Fryer Metos Lightfry

## LF12EM 440V/3PE/60

**MG4001554MM**

Metos Lightfry is a commercial air fryer for making crispy french fries and all kinds of finger food without adding even a single drop of oil. Steam, hot air and motion are used instead.

The cooking process is divided into two steps. First, a steam phase during which the product is thoroughly cooked. The second phase is the crisp phase, during which a fan with hot and dry air gives a crispy surface. Everything happens in a rotating basket in a closed oven chamber. The fryer uses up to 50% less energy and offers a better working environment than a deep fat fryer. Depending on the type of food used in the air fryer, you can offer up to 100% less fat in the food you are serving. With the Metos Lightfry airfryer, you do not need any installation or maintenance of a fire fighting system above the unit, such as in Deep Fat Fryers. You also eliminate the risk of the operators of the galley getting scolded by hot oil when there is rough sea.

- Up to 100% less fat in food as only steam and hot air is used
- Gives the food a crispy surface
- Low risk of fire
- Less environmental impact
- Automatic emptying and integrated cleaning system
- No oil change, deliveries or destruction
- Stainless steel oven and casing
- 7,5 min to cook 2 kg french fries



## Fryer Metos Lightfry LF12EM 440V/3PE/60

Item width mm	693
Item depth mm	645
Item height mm	711
Net volume l	22kg/h
Package volume	0.446
Unit of volume	m3
Package volume	0.446 m3
Package length	75
Package width	70
Package height	85
Package unit of dimension	cm
Package dimensions (LxWxH)	75x70x85 cm
Net weight	107
Net weight	107 kg
Gross weight	130
Package weight	130 kg
Unit of weight	kg
Connection power kW	16
Fuse Size A	25
Connection voltage V	440
Number of phases	3PE
Frequency Hz	60
Protection rating (IP)	22
Type of electrical connection	Semifixed
Cold water diam.	3/4"
Cold water min pressure kPa	400
Cold water max pressure kPa	600
Cold water conn. inlet	Bottom;Behind
Drain conn. inlet	Bottom

**Fryer Metos Lightfry LF12EM 440V/3PE/60**

Sound level dB	67
Operation type	electronical
Temperature area °C	max 260°C
Top material type	stainless steel