

## Dryer Primus T24 440/3PE/60 Marine

## MG4160762MM

Drum diameter  $\varnothing$  930mm. Anthracite grey skinplate front and side

- Standard stainless steel drum with large diameter
- Easy-to-use microprocessor: Easy Control
- Radial airflow with PowerDry® maximal heat transfer
- low energy consumption
- short drying time
- Large door opening (Ø80cm) for easy loading and unloading
- Self cleaning lint screen

Options (not included in the price)

- Reversing drum
- Full Control programmer
- Residual moisture control Sensodry®: ,,- safe drying of delicate linen ,,- humidity detection in % ,,- ideal in combination with SoftWash® ,,- ideal for dry cleaners, fire departments
- available on Full Control





## Dryer Primus T24 440/3PE/60 Marine

Product capacity	24kg
Item width mm	965
Item depth mm	1270
Item height mm	1975
Package volume	2.849
Unit of volume	m3
Package volume	2.849 m3
Package length	104
Package width	132
Package height	207.5
Package unit of dimension	cm
Package dimensions (LxWxH)	104x132x207.5 cm
Net weight	275
Net weight	275 kg
Gross weight	300
Package weight	300 kg
Unit of weight	kg
Connection power kW	30
Connection voltage V	440
Number of phases	3PE
Frequency Hz	60
Protection rating (IP)	43
Type of electrical connection	Semifixed