

Washer extractor Primus RX80 400/3PE/50 Marine

MG4160775MK

Capacity 8kg. Wash speed 50

- Extraction: 820 rpm
- Stainless steel top and front panel (AISI 304)
- Xcontrol - easy to use microprocessor
- Rigid mounted, normal speed 100 G-factor
- Stainless steel drum and tub
- Stainless steel top and front panels
- Anthracite skinplate side panels
- Soap hopper and opening
- With Liquid Soap Print
- Easy access to all vital parts from the front
- Patented soap hopper
- Large drain valve (Ø76 mm)
- Compact width: 660 mm, ideal for replacing existing models (including models of most competitors)
- Frequency controlled motor
- PowerWash® perforated lifting ribs more mechanical action, lower water consumption
- Measurement of unbalance by means of frequency inverter
- SuperEco washing programmes
- significantly reduces water and electricity consumption

OPTIONS

- Xcontrol Plus - Fully programmable
- Coin operated timer (CPS)
- USB plug (on the back panel)
- Easy Soap - liquid soaps connection
- Liquid soap pumps
- Water recovery kit
- Steam heating version
- Drain pump (RX80)
- 3rd water inlet



Washer extractor Primus RX80 400/3PE/50 Marine

Product capacity	Max. 9 kg
Item width mm	660
Item depth mm	785
Item height mm	1115
Package volume	0.668
Unit of volume	m3
Package volume	0.668 m3
Package length	67
Package width	79.5
Package height	125.5
Package unit of dimension	cm
Package dimensions (LxWxH)	67x79.5x125.5 cm
Net weight	135
Net weight	135 kg
Gross weight	145
Package weight	145 kg
Unit of weight	kg
Connection power kW	6
Connection voltage V	400
Number of phases	3PE
Frequency Hz	50
Protection rating (IP)	44
Type of electrical connection	Semifixed
Electrical conn. height mm	1025
Cold water diam.	3/4"
Cold water min pressure kPa	500
Cold water conn. height mm	916
Drain diameter	3
Drain flow l/s	3

Washer extractor Primus RX80 400/3PE/50 Marine

Drain conn. height mm	88
Floor drain needed	Yes
Sound level dB	64