

# Washer extractor Primus RX180 400/3PE/50 Marine

#### MG4160790MK

Capacity 18kg. Wash speed 42

- Exraction: 490rpm
- Stainless steel top and fron panel (AISI 304)
- Xcontrol easy to use microprocessor
- Rigid mounted, normal speed 100 G-factor
- Stainless steel drum and tub
- Stainless steel top and front panels
- Anthracite skinplate side panels
- With a hole for soap hopper
- With Liquid Soap Print
- Easy access to all vital parts from the front
- Patented soap hopper
- Large drain valve (Ø76 mm)
- Frequency controlled motor
- PowerWash® perforated lifting ribs more mechanical action, lower water consumption  $% \left( 1\right) =\left( 1\right) +\left( 1\right$
- Measurement of unbalance by means of frequency invertor
- SuperEco washing programmes
- significantly reduces water and electricity consumption
- Easy Soap liquid soaps connection with control board 8x24VAC signals

### **OPTIONS**

- Xcontrol Plus Fully programmable
- Coin operated timer (CPS)
- USB plug (on the back panel)
- Water recovery kit
- Steam heating version
- Drain pump (RX80)
- 3rd water inlet





## Washer extractor Primus RX180 400/3PE/50 Marine

| Product capacity              | Max. 20 kg     |
|-------------------------------|----------------|
| Item width mm                 | 890            |
| Item depth mm                 | 915            |
| Item height mm                | 1410           |
| Package volume                | 1.182          |
| Unit of volume                | m3             |
| Package volume                | 1.182 m3       |
| Package length                | 90             |
| Package width                 | 92.5           |
| Package height                | 142            |
| Package unit of dimension     | cm             |
| Package dimensions (LxWxH)    | 90x92.5x142 cm |
| Net weight                    | 270            |
| Net weight                    | 270 kg         |
| Gross weight                  | 290            |
| Package weight                | 290 kg         |
| Unit of weight                | kg             |
| Connection power kW           | 12             |
| Connection voltage V          | 400            |
| Number of phases              | 3PE            |
| Frequency Hz                  | 50             |
| Protection rating (IP)        | 44             |
| Type of electrical connection | Semifixed      |
| Electrical conn. height mm    | 1317           |
| Cold water diam.              | 3/4"           |
| Cold water min pressure kPa   | 500            |
| Cold water conn. height mm    | 1212           |
| Drain diameter                | 3              |
| Drain flow I/s                | 3              |
|                               |                |

## Washer extractor Primus RX180 400/3PE/50 Marine

| Drain conn. height mm | 130 |
|-----------------------|-----|
| Floor drain needed    | Yes |