

# Washer extractor Metos RX180 440V

**MG4160790MM**

Capacity 18kg. Wash speed 42

- Extraction: 490rpm
- Stainless steel top and front panel (AISI 304)
- Anthracite skinplate side panels
- With a hole for soap hopper
- With Liquid Soap Print
- Xcontrol - easy to use microprocessor
- Rigid mounted, normal speed 100 G-factor
- Stainless steel drum and tub
- Easy access to all vital parts from the front
- Patented soap hopper
- Large drain valve (Ø76 mm)
- Frequency controlled motor
- PowerWash® perforated lifting ribs more mechanical action, lower water consumption
- Measurement of unbalance by means of frequency inverter
- SuperEco washing programmes
- significantly reduces water and electricity consumption

## OPTIONS

- Xcontrol Plus - Fully programmable
- Coin operated timer (CPS)
- USB plug (on the back panel)
- Easy Soap - liquid soaps connection
- Liquid soap pumps
- Water recovery kit
- Steam heating version
- Drain pump (RX80)
- 3rd water inlet



## Washer extractor Metos RX180 440V

|                               |                      |
|-------------------------------|----------------------|
| Product capacity              | Max. 20 kg           |
| Item width mm                 | 890                  |
| Item depth mm                 | 915                  |
| Item height mm                | 1410                 |
| Package volume                | 1.182                |
| Unit of volume                | m <sup>3</sup>       |
| Package volume                | 1.182 m <sup>3</sup> |
| Package length                | 90                   |
| Package width                 | 92.5                 |
| Package height                | 142                  |
| Package unit of dimension     | cm                   |
| Package dimensions (LxWxH)    | 90x92.5x142 cm       |
| Net weight                    | 255                  |
| Net weight                    | 255 kg               |
| Gross weight                  | 290                  |
| Package weight                | 290 kg               |
| Unit of weight                | kg                   |
| Connection power kW           | 12                   |
| Connection voltage V          | 440-480              |
| Number of phases              | 3PE                  |
| Frequency Hz                  | 60                   |
| Protection rating (IP)        | 44                   |
| Type of electrical connection | Semifixed            |
| Electrical conn. height mm    | 1317                 |
| Cold water diam.              | 3/4"                 |
| Cold water min pressure kPa   | 500                  |
| Cold water conn. height mm    | 1212                 |
| Drain diameter                | 3                    |
| Drain flow l/s                | 3                    |

Washer extractor Metos RX180 440V

|                       |     |
|-----------------------|-----|
| Drain conn. height mm | 130 |
| Floor drain needed    | Yes |