

Washer extractor Primus RX240 440/3PE/60 Marine

MG4160795MM

Capacity 240 liters. Wash speed 42

- Extraction: 490rpm
- Stainless steel top and front panel (AISI 304)
- Anthracite skinplate side panels
- Xcontrol - easy to use microprocessor
- Rigid mounted, medium spin 100 G-factor
- Stainless steel drum and tub
- Easy access to all vital parts from the front
- Patented soap hopper
- A hole for soap hopper
- With Liquid Soap Print
- Large drain valve (Ø76 mm)
- Frequency controlled motor
- PowerWash® perforated lifting ribs more mechanical action, lower water consumption
- Measurement of unbalance by means of frequency inverter
- SuperEco washing programmes
- significantly reduces water and electricity consumption

OPTIONS

- Xcontrol Plus - Fully programmable
- Coin operated timer (CPS)
- USB plug (on the back panel)
- Easy Soap - liquid soaps connection
- Liquid soap pumps
- Water recovery kit
- Steam heating version
- Drain pump (RX80)
- 3rd water inlet



Washer extractor Primus RX240 440/3PE/60 Marine

Product capacity	25 kg
Item width mm	890
Item depth mm	1060
Item height mm	1410
Package volume	1.367
Unit of volume	m3
Package volume	1.367 m3
Package length	90
Package width	107
Package height	142
Package unit of dimension	cm
Package dimensions (LxWxH)	90x107x142 cm
Net weight	290
Net weight	290 kg
Gross weight	315
Package weight	315 kg
Unit of weight	kg
Connection power kW	18
Connection voltage V	440-480
Number of phases	3PE
Frequency Hz	60
Protection rating (IP)	44
Type of electrical connection	Semifixed
Electrical conn. height mm	1260
Cold water diam.	3/4"
Cold water min pressure kPa	500
Cold water conn. height mm	1297
Drain diameter	3
Drain flow l/s	3

Washer extractor Primus RX240 440/3PE/60 Marine

Drain conn. height mm	130
Floor drain needed	Yes