

Washer extractor Primus RX280 440/3PE/60 Marine

MG4160800MM

Capacity 280 litres. Wash speed 42

- Extraction: 490rpm
- Stainless steel top and front panel (AISI 304)
- Xcontrol - easy to use microprocessor
- Rigid mounted, medium spin 100 G-factor
- Stainless steel drum and tub
- Easy access to all vital parts from the front
- Patented soap hopper
- With Liquid Soap Print
- Large drain valve (Ø76 mm)
- Frequency controlled motor
- PowerWash® perforated lifting ribs more mechanical action, lower water consumption
- Measurement of unbalance by means of frequency inverter
- SuperEco washing programmes
- significantly reduces water and electricity consumption

OPTIONS

- Xcontrol Plus - Fully programmable
- Coin operated timer (CPS)
- USB plug (on the back panel)
- Easy Soap - liquid soaps connection
- Liquid soap pumps
- Water recovery kit
- Steam heating version
- Drain pump (RX80)
- 3rd water inlet



Washer extractor Primus RX280 440/3PE/60 Marine

Product capacity	Max. 32 kg
Item width mm	890
Item depth mm	1135
Item height mm	1410
Package volume	1.463
Unit of volume	m3
Package volume	1.463 m3
Package length	90
Package width	114.5
Package height	142
Package unit of dimension	cm
Package dimensions (LxWxH)	90x114.5x142 cm
Net weight	305
Net weight	305 kg
Gross weight	335
Package weight	335 kg
Unit of weight	kg
Connection power kW	23.2
Fuse Size A	40
Connection voltage V	440-480
Number of phases	3PE
Frequency Hz	60
Protection rating (IP)	44
Type of electrical connection	Semifixed
Electrical conn. height mm	1317
Cold water diam.	3/4"
Cold water min pressure kPa	500
Cold water conn. height mm	1212
Drain diameter	3

Washer extractor Primus RX280 440/3PE/60 Marine

Drain flow l/s	3
Drain conn. height mm	130
Floor drain needed	Yes