

# Water cooler River 30 IB C G63-61C6 50-60Hz R290

**MG4164034MP**

River is the drinking fountain that ensures constant quality over time with very little maintenance. It can be easily installed in public venues, like offices, waiting rooms, schools and shopping centers. This water cooler always ensures fresh and cold water to be dispensed. The wide range of taps makes it possible to drink directly from the jet and/or using a cup. The sink also features a drainage system. The pre-filled ice bank simplifies the installation procedure; it is filled during the production process and sealed to avoid evaporation or accidental water leaks during transportation.

- floor-standing model
- thermostat controlled system
- 30 liters of +8-12°C water/hour
- smooth surface and rounded corners makes it easy to clean

The benefits of a drinking fountain with a highly efficient filtration system:

- always safe drinking water
- sustainable
- cost savings
- improve the taste of drinking water



## Water cooler River 30 IB C G63-61C6 50-60Hz R290

|                               |                           |
|-------------------------------|---------------------------|
| Product capacity              | 30 liters +8-12°C water/h |
| Item width mm                 | 325                       |
| Item depth mm                 | 340                       |
| Item height mm                | 960/1230                  |
| Package volume                | 0.178                     |
| Unit of volume                | m3                        |
| Package volume                | 0.178 m3                  |
| Package length                | 40                        |
| Package width                 | 42                        |
| Package height                | 106                       |
| Package unit of dimension     | cm                        |
| Package dimensions (LxWxH)    | 40x42x106 cm              |
| Net weight                    | 26                        |
| Net weight                    | 26 kg                     |
| Gross weight                  | 28                        |
| Package weight                | 28 kg                     |
| Unit of weight                | kg                        |
| Connection power kW           | 0.184                     |
| Connection voltage V          | 220-240                   |
| Number of phases              | 1PE                       |
| Frequency Hz                  | 50/60                     |
| Protection rating (IP)        | 21                        |
| Type of electrical connection | Plug                      |
| Type of the refrigerant       | R290                      |
| Quantity of refrigerant g     | 40                        |