

Bulk brewer Metos ComBi-line 2x20W NG 400V pilot voltage 230V

MG4170754MKA

The Metos CB 2x20W NG counter top model is an easy to use, fast and reliable coffee maker with one filtering unit, hot water tap and two twenty litres containers . With its help, you will be able to brew a container full of delicious filtered coffee in fifteen minutes.

The amount of coffee to be prepared can be selected in either litres or cups from the easy to use, touch sensitive panel. The unit's touch panel helps users when it comes to using the coffee brewer and adding the correct amount of coffee powder. The coffee brewer is equipped with a timer, with the aid of which the brewing of filtered coffee can be programmed to start at a certain time. The coffee maker is capable of brewing around 90 litres (approx. 720 cups) of coffee per hour. The brewing of filtered coffee will not begin if the jug is not in place and the filter bracket has not been rotated into position above the jug. The process of brewing filtered coffee can be monitored on the panel. The general and daily consumption of coffee and coffee powder can be monitored on the panel. When the coffee is ready, the coffee maker will let you know on the panel and with an audio signal. The measuring gauge of the electrically heated container shows how much coffee is left.

The water temperature of the hot water tap located in housing of the coffee maker can be regulated between 60 °C...97 °C; the factory setting is 90 °C. Output is 60 litres of hot water per hour, with a maximum of 4 ,1 litres dispensed at one time. The insulated boiler has a capacity of 5,6 litres. If hot water has



not been used in the last two hours, the energy saving function lowers the temperature of the hot water to 60 °C.

The Metos CB 2x20W NG coffee maker with container operates on the principle of flow through heating, which means that the device uses only cold and oxygen rich water during filtering, and maintains the correct temperature for water throughout the filtering processes. The indicator, which is adjusted depending on water hardness, displays the need for removing scale deposits from the coffee maker.

The coffee maker's housing and the containers are made from stainless steel, and the front parts are made from aluminium. The containers are located on the both sides of the coffee maker housing. The power connection of the insulated, electrically heated container is connected to a socket located in the housing of the coffee pot and protected from splashing.

- containers capacity 20 l
- with fixing brackets and storm rail for container
- hot water tap
- filtered coffee brewing capacity around 90 l/h (approx. 720 cups), hot water 60 l/h
- the amount of brewed filtered coffee can be selected in litres or number of cups
- filtered coffee brewing audio signal
- indicator indicating the need to remove scale deposits
- filtering bracket's boundary sensor
- container sensor
- hot water temperature can be regulated between 60 °C...97 °C
- touch sensitive screen
- table top model
- the containers are located on the left side of the coffee maker housing

SUPPLIED SET INCLUDES:

-- 2 electrically heated coffee container, with a seal equipped lid

-- 2 filtering unit with a filtering block

-- 2 mixing pipe

- power cord for the containers

-- drip tray

-- gauge glass brush

-- measuring glass

- coffee, tea and hot water stickers

EXTRA ACCESSORIES (can be ordered separately):

-- filter paper 203/533 (500 pcs per pack)

-- tea filter and filling pipe

- additional containers not been used in the last two hours, the energy saving function lowers the temperature of the hot water to 60 °C.

The Metos CB 2x20W NG coffee maker with container operates on the principle of flow through heating, which means that the device uses only cold and oxygen rich water during filtering, and maintains the correct

temperature for water throughout the filtering processes. The indicator, which is adjusted depending on water hardness, displays the need for removing scale deposits from the coffee maker.

The coffee maker's housing and the containers are made from stainless steel, and the front parts are made from aluminium. The containers are located on the both sides of the coffee maker housing. The power connection of the insulated, electrically heated container is connected to a socket located in the housing of the coffee pot and protected from splashing.

- containers capacity 20 l
- with fixing brackets and storm rail for container
- hot water tap
- filtered coffee brewing capacity around 90 l/h (approx. 720 cups), hot water 60 l/h
- the amount of brewed filtered coffee can be selected in litres or number of cups
- filtered coffee brewing audio signal
- indicator indicating the need to remove scale deposits
- filtering bracket's boundary sensor
- container sensor
- hot water temperature can be regulated between 60 °C...97 °C
- touch sensitive screen
- table top model
- the containers are located on the left side of the coffee maker housing

SUPPLIED SET INCLUDES:

- 2 electrically heated coffee container, with a seal equipped lid
- 2 filtering unit with a filtering block
- 2 mixing pipe
- power cord for the containers
- drip tray
- gauge glass brush
- measuring glass
- coffee, tea and hot water stickers

EXTRA ACCESSORIES (can be ordered separately):

- filter paper 203/533 (500 pcs per pack)
- tea filter and filling pipe
- additional containers

Bulk brewer Metos ComBi-line 2x20W NG 400V pilot voltage 230V

Product capacity	90 l coffee, 22 l hot water /h
Item width mm	1095
Item depth mm	500(360)
Item height mm	895
Package volume	0.49
Unit of volume	m3
Package volume	0.49 m3
Package length	103.5
Package width	52
Package height	91
Package unit of dimension	cm
Package dimensions (LxWxH)	103.5x52x91 cm
Net weight	45
Net weight	45 kg
Gross weight	50
Package weight	50 kg
Unit of weight	kg
Connection power kW	9.275
Fuse Size A	16
Connection voltage V	380-415
Number of phases	3NPE
Frequency Hz	50/60
Type of electrical connection	Semifixed
Electrical conn. height mm	25
Remarks (electrical)	pilot voltage 230V
Cold water diam.	19
Cold water flow l/min	5
Cold water min pressure kPa	200
Cold water conn. height mm	25

Bulk brewer Metos ComBi-line 2x20W NG 400V pilot voltage 230V

Floor drain needed	Yes
Coffee type	Filtering coffee