

Cold cabinet MBC-300R

230/1/50-60

MG4209724MP

Temperature zone: +1...+10 °C. CFC-free insulation and refrigerant R290

- stainless steel interior and exterior
- specially designed for marine use
- durable hinges
- cold unit on the upper part of the cabinet
- automatic temperature control and electronic thermostat with number display
- automatic defrost and evaporation of condense water
- stainless steel shelves, 3 pcs, size 450 mm x 450 mm
- interior lighting
- lockable door, right-handed



Cold cabinet MBC-300R 230/1/50-60

Product capacity	300 litres
Item width mm	610
Item depth mm	670
Item height mm	1600/1640
Net volume l	260 liter acc. to EN16825
Package volume	0.884
Unit of volume	m3
Package volume	0.884 m3
Package length	69
Package width	72
Package height	178
Package unit of dimension	cm
Package dimensions (LxWxH)	69x72x178 cm
Net weight	82
Net weight	82 kg
Gross weight	88
Package weight	88 kg
Unit of weight	kg
Connection power kW	0.32
Fuse Size A	6
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60
Protection rating (IP)	44
Type of electrical connection	Plug
Type of the refrigerant	R290
Quantity of refrigerant g	80
Sound level dB	45