

Dishwasher Metos LUX 60EL

MG4246051MM

High-Tech double skin under-counter dishwasher is designed for heavy duty use in professional kitchens and restaurants. The digital control panel is easy to use and its signal lights indicate the different cycles. Diagnostic function supports self-monitoring.

- hot or cold water connection
- four wash programs (1, 2, 3 and 5 minutes)
- automatic cleaning program
- max height for dishes 325 mm
- able to wash GN1/1 container
- signal lights indicate the different cycles and temperatures
- diagnostic function ensures a sufficiently high temperature in the final rinse
- rounded edges in the tank facilitate cleaning
- easy to remove wash arm
- acoustic and thermal insulation keeps the noise level and the surface temperature low
- rack size 500x500 mm

Delivery includes:

- detergent dispenser
- rinse aid dispenser
- basket for plates
- basket for glasses
- cutlery holder
- connection hose for tap water
- Soft start: progressive start of the wash pump
- Marine feet + lock

Optional (to be ordered separately):

- Drain pump
- extra racks
- pre-wash tables and basket trolleys



Dishwasher Metos LUX 60EL

| | |
|-------------------------------|-------------|
| Item width mm | 600 |
| Item depth mm | 610 |
| Item height mm | 850 |
| Package volume | 0.451 |
| Unit of volume | m3 |
| Package volume | 0.451 m3 |
| Package length | 68 |
| Package width | 67 |
| Package height | 99 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 68x67x99 cm |
| Net weight | 63.5 |
| Net weight | 63.5 kg |
| Gross weight | 70 |
| Package weight | 70 kg |
| Unit of weight | kg |
| Connection power kW | 5.15 |
| Fuse Size A | 16 |
| Connection voltage V | 440 |
| Number of phases | 3PE |
| Frequency Hz | 60 |
| Protection rating (IP) | 24 |
| Type of electrical connection | Semifixed |
| Electrical conn. height mm | 45 |
| Cold water conn. height mm | 65 |
| Hot water diam. | 3/4" |
| Hot water flow l/min | 10 |
| Hot water conn. height mm | 45 |
| Drain diameter | 30 |

Dishwasher Metos LUX 60EL

| | |
|-----------------------|------------------------------------|
| Drain flow l/s | 3 |
| Drain conn. height mm | 65 |
| Water consumption | Water consumption litres/cycle 2.3 |