

Dishwasher Metos LUX

60EL PS 400/3/50

MG4246052MK

High-Tech double skin under-counter dishwasher is designed for heavy duty use in professional kitchens and restaurants. The digital control panel is easy to use and its signal lights indicate the different cycles. Diagnostic function supports self-monitoring.

The dishwasher is equipped with a drain pump, in which case the wash water can be discharged into the washing counter sink.

- hot or cold water connection
- four wash programs (1, 2, 3 and 5 minutes)
- automatic cleaning program
- max height for dishes 325 mm
- able to wash GN1/1 container
- signal lights indicate the different cycles and temperatures
- diagnostic function ensures a sufficiently high temperature in the final rinse
- rounded edges in the tank facilitate cleaning
- easy to remove wash arm
- acoustic and thermal insulation keeps the noise level and the surface temperature low

Delivery includes:

- detergent dispenser
- rinse aid dispenser
- basket for plates
- basket for glasses
- cutlery holder
- connection hose for tap water
- Soft start: progressive start of the wash pump
- Drain pump
- Marine feet + lock

Optional (to be ordered separately):

- extra racks
- pre-wash tables and basket trolleys



Dishwasher Metos LUX 60EL PS 400/3/50

Item width mm	600
Item depth mm	610
Item height mm	850
Package volume	0.451
Unit of volume	m3
Package volume	0.451 m3
Package length	68
Package width	67
Package height	99
Package unit of dimension	cm
Package dimensions (LxWxH)	68x67x99 cm
Net weight	63.5
Net weight	63.5 kg
Gross weight	72
Package weight	72 kg
Unit of weight	kg
Connection power kW	5.15
Fuse Size A	16
Connection voltage V	400
Number of phases	3PE
Frequency Hz	50
Protection rating (IP)	24
Type of electrical connection	Semifixed
Electrical conn. height mm	45
Cold water conn. height mm	65
Hot water diam.	3/4"
Hot water flow l/min	10
Hot water conn. height mm	45
Drain diameter	30

Dishwasher Metos LUX 60EL PS 400/3/50

Drain flow l/s	3
Drain conn. height mm	65
Water consumption	Water consumption litres/cycle 2.3