

Dishwasher Metos WD-6+DD 400/3PE/50 Marine

MG4246076

Hoodtype of dishwasher. Noise and heat insulated

- electronic control
- three washing cycles. Possibility to programme washing and rinsing times as well as rinsing temperatures. This makes it possible to have e.g. an own programme for fine porcelain having a lower rinse temperature
- hygiene warranty; machine indicates too low temperatures and continues washing if rinsing temperature is too low
- good rinsing result is always secured; machine controls the rinse water flow and it indicates too low a flow to the user
- easy to use; machine warns of a closed tap and of a misplaced overflow tube
- digital control panel shows the daily and total amount of washed racks; it also displays the programme, temperatures and washing time remaining
- easy to keep clean; automatical cleaning programme
- unique hood prevents the steam from evacuating against the face of the user when the hood is opened
- wash arm empties it self from washing water when rinsing starts,this quarantees a sparkling rinsing result
- washing arms are self cleaning
- rack size 500 x 500 mm
- washing cycle starts when the hood is closed
- tank volume 50 l

Standard equipment:

- rinse aid dispenser
- plate rack
- cup rack
- utensil rack
- detergent dispenser for liquid detergent

Extra equipment:

- water connection pipe with stop cock, non-return and vacuum valves
- steam hood which is connected to the machine; steam is released to the ventilation channel instead of the dishwashing room



machine with a booster pump

- machine with a drain pump
- cold water connected machine
- automatic control of the ventilation fan machine with a booster pump
- machine with a drain pump
- cold water connected machine
- automatic control of the ventilation fan



Dishwasher Metos WD-6+DD 400/3PE/50 Marine

em depth mm 6 em height mm 1	600/695 657/700 1430/1880
em height mm	
9	1430/1880
olko go volumo	
ackage volume	0.847
nit of volume r	m3
ackage volume (0.847 m3
ackage length 7	76.5
ackage width 7	71
ackage height	156
ackage unit of dimension	cm
ackage dimensions (LxWxH)	76.5x71x156 cm
et weight 9	93
et weight S	93 kg
ross weight 1	115
ackage weight	115 kg
nit of weight k	kg
onnection power kW	9.75
ise Size A	16
onnection voltage V	400
umber of phases	3PE
equency Hz	50
pe of electrical connection	Semifixed
ot water diam.	1/2"
ot water flow I/min	18
ot water conn. height mm	200
rain diameter 5	50
rain flow I/s	3
rain conn. height mm	30

Dishwasher Metos WD-6+DD 400/3PE/50 Marine

Water consumption

water consumption, rinse (litres/programme) 4