

# Range+oven Metos

## RP4/Chef220 3/PE~400V

### 50Hz Mar

MG4210464MK

Cooking plates made of cast iron, external surfaces stainless steel. Four 3 kW cooking plates, size 300x300 mm

- hinged plates make cleaning easy
- 7-steps power regulator
- signal lights
- storm rail in front of the range
- pot rack

Stand with Metos Chef 220 roasting oven:

- cooking cabinet, door and external surfaces stainless steel
- temperature: +50-300°C
- timer 0-120 min or continuous
- capacity 1 x GN2/1 or 2 x GN1/1



## Range+oven Metos RP4/Chef220 3/PE~400V 50Hz Mar

|                               |                       |
|-------------------------------|-----------------------|
| Product capacity              | 1x GN2/1              |
| Item width mm                 | 800                   |
| Item depth mm                 | 800                   |
| Item height mm                | 900                   |
| Package volume                | 0.81                  |
| Unit of volume                | m3                    |
| Package volume                | 0.81 m3               |
| Package length                | 90                    |
| Package width                 | 90                    |
| Package height                | 100                   |
| Package unit of dimension     | cm                    |
| Package dimensions (LxWxH)    | 90x90x100 cm          |
| Net weight                    | 125                   |
| Net weight                    | 125 kg                |
| Gross weight                  | 170                   |
| Package weight                | 170 kg                |
| Unit of weight                | kg                    |
| Connection power kW           | 14.9                  |
| Fuse Size A                   | 25                    |
| Connection voltage V          | 400                   |
| Number of phases              | 3PE                   |
| Frequency Hz                  | 50/60                 |
| Startup current A             | 22.6                  |
| Protection rating (IP)        | X4                    |
| Type of electrical connection | Semifixed             |
| Electrical conn. height mm    | 160                   |
| Remarks (electrical)          | Working current 22,6A |