

Range IE6 3/PE~440V 60Hz

Mar

MG4210604MM

Induction range, 6 zones Diameter of the zones 260 mm. Made completely out of stainless steel. On an open stand with a stainless shelf.

- storm rail in front of the range
- pot rack
- marinelegs

Fast, efficient and safe.

- Induction range produces virtually no excess heat to the kitchen
- Considerably faster than an electric or gas range
- Immediate reaction to power adjustment
- The range itself does not warm up and is always cooler than the cooking vessel
- Spill-overs do not burn in the cool surfaces
- Heat is produced only when a cooking vessel with min diam. 120mm is on the zone
- Energy consumption significantly lower than that of an electric range

Because of the operating principle, the cooking vessels used must have a magnetic bottom. Best results can be achieved with steel vessels with either sandwich or compoind bottom. Most cast iron cooking vessels work. Aluminium vessels are not recommended and they usually do not work.



Range IE6 3/PE~440V 60Hz Mar

Product capacity	6 cooking zones
Item width mm	800
Item depth mm	1200
Item height mm	900
Package volume	1.217
Unit of volume	m3
Package volume	1.217 m3
Package length	126
Package width	92
Package height	100
Package unit of dimension	cm
Package dimensions (LxWxH)	126x92x100 cm
Net weight	85
Net weight	85 kg
Gross weight	140
Package weight	140 kg
Unit of weight	kg
Connection power kW	21
Fuse Size A	32
Connection voltage V	440
Number of phases	3PE
Frequency Hz	60
Startup current A	29.3
Protection rating (IP)	X3
Type of electrical connection	Semifixed
Remarks (electrical)	Working current 29,3A
Type	induction