

Rack conveyor machine

METOS WD-151E TOUCH R-L 400/3PE/50Hz Marine

MG4246275MK

Metos WD 151E TOUCH- Rack conveyor machine is reliable and cost-effective rack conveyor machine with unique basket feed system allows operators to adjust their contact time and the capacity depending on how heavily soiled the dishware is. TOUCH DISPLAY is self-explanatory and angled, made in tempered glass. Works even if you are wearing gloves or have wet hands.



Feeding direction right-left, length 1655mm incl. Loading hood 170mm, Chemical wash 900mm, Triple final rinse 585mm.

- Infeed size 538'440mm
 - User-friendly - Ergonomically designed to provide a good working environment
 - The WD-Touch display guides you through the washing process with an intuitive touch screen and ensures the washing temperature. Easy navigation with built-in user manuals. Quick error reporting simplifies servicing and minimizes unnecessary downtime.
 - Low operating costs and a reduced environmental impact
 - Triple rinse for reduced final rinse water consumption
 - Excellent wash results - Long washing zones with powerful pumps
 - Long service life and easy servicing- Made entirely of stainless steel
 - Improved hygiene with vertical self-emptying wash- and rinse pumps
 - Electrical connection of PRE-RINSE by the dishwasher
 - PRE-RINSE using excess water from the dishwasher
 - Electricity and water connections from top
 - Drain integrated in the machine for easy cleaning and draining
 - ECO-FLOW - condensing unit with heat recovery by the exhausted steam
 - Wash arms in stainless steel, with quick fit/ removal function.
- Easily

cleaned and without end covers

- Removable doors for the periodical cleaning
- Easy servicing - the machine is serviced from the front
- Single lever for emptying the tanks, automatic closing of tanks when refilling is starting
- Monitoring system of the machine's various functions
- Panel which displays the information
- Web Tool with HACCP documentation
- Contactor for entry and exit conveyor. Note! It's always necessary to specify the motor power of the conveyor. If not specified, protective motor switch of 0,63-1A will be delivered.

OPTIONS

- Pre-rinse zone L=400 mm
- Drying zone WD-T60 L=600 mm, insulated. Power 3,3 kW.
- ,, Stand with grid shelf Stand with plane shelf
- Drying zone WD-T80, to turn track L=820 mm, insulated, for connection to the or machine driven WD turn track. Power 3,3 kW.
- Double drying zone WD-T90 L=900 mm, insulated. With stand. Power 6,6 kW.
- Grid shelf
- Plane shelf
- Divided between machine and drying zone
- 230V/3/50Hz
- Marine version and other voltage selection on request
- Steam heated design, steam pressure 50-149 kPa
- Steam heated design, steam pressure 150 - 250 kPa
- Break tank included with booster pump
- Booster heater 12 kW for re-circulating final rinse
- RO-water connection
- Stainless pipes and couplings in final rinse
- Cold water connection
- Water connection from floor
- Timer for pre-rinse
- Timer for through-rinse
- Timer for chain-rinse
- Timer start, machine ready for wash
- Contactor for control of pre-rinse without timer
- Contactor for pre-rinse with booster pump
- Connection power restriction for example Sicotronic
- External power indication
- Auto self-cleaning of wash zone
- Auto self-cleaning of condense battery
- Auto self-cleaning of wash zone + condenser battery
- Web Tool with HACCP documentation for cost- and consumption report
- Possibility to interlock the booster heater

EXTRA EQUIPMENT

- Ask more from Metos Sales
- Conduit for connection cable, L=1200 mm

TECHNICAL DATA

- Pump, pre-wash (kW) -
- Pump, chemical wash 1 (kW) 1.5
- Pump, chemical

wash 2 (kW) -

- Pump, chemical wash 3 (kW) -
- Pump, recirculating final rinse (kW) 0.11
- Fan, heat recovery (kW) 0.12
- Motor, feeder (kW) 0.12
- Booster heater 1 (kW) 9
- Booster heater 2 (kW) 9
- Heater, chemical wash 1 (kW) 12
- Heater, chemical wash 2 (kW) -
- Heater, chemical wash 3 (kW) -
- Heat recovery unit, cooling area (m²) 25
- Fan heat recovery, capacity (m³/h) 100
- Tank volume, pre-wash tank (liters) -
- Tank volume, wash tank 1 (liters) 100
- Tank volume, wash tank 2 (liters) -
- Tank volume, wash tank 3 (liters) -
- Tank volume, final rinse tank (liters) 6
- Weight, dishwasher in operation (kg) 490
- Degree of protection (IP) 55
- Total connected power (kW) interlocked booster heater (kW) 23,6
- Total connected power (kW) 32.6
- Main fuse 400V 3N~(A)* 50
- Max. connection area 400V 3N~(L1-L3, N, PE) Cu (mm²) 35,,
- Hot water connection 50-65°C (internal thread) R ½"
- Cold water connection 5-12°C (internal thread) R ½"
- Drain connection, PP pipe (ø mm) 50
- Water capacity, pressure (kPa) 250-600
- Water capacity, flow (liters/min) 11
- Floor drain, capacity (liters/sec) 3
- Heat load to the room (total, sensible, latent) (kW) 7.5 / 4.5 / 3.0

CAPACITY AND OPERATING DATA

- Capacity normal wash (baskets/h) 70-150*
- Capacity according to DIN 10510 (baskets/h) 80
- Max capacity interlocked booster heater (baskets/h) 150
- Cold water consumption, final rinse normal (liters/basket) 1.5
- Sound level (dB) 68

... more details on our web pages

Rack conveyor machine METOS WD-151E TOUCH R-L 400/3PE/50Hz Marine

Product capacity	80 basket/hour (DIN 10510)
Item width mm	1655
Item depth mm	697
Item height mm	1675/1950
Package volume	3.36
Unit of volume	m3
Package volume	3.36 m3
Package length	210
Package width	80
Package height	200
Package unit of dimension	cm
Package dimensions (LxWxH)	210x80x200 cm
Net weight	370
Net weight	370 kg
Gross weight	400
Package weight	400 kg
Unit of weight	kg
Connection power kW	32.6
Fuse Size A	50
Connection voltage V	400
Number of phases	3PE
Frequency Hz	50
Protection rating (IP)	55
Cold water diam.	1/2"
Cold water flow l/min	11
Cold water min pressure kPa	250
Cold water max pressure kPa	600
Hot water diam.	1/2"
Hot water thread	Internal thread

Rack conveyor machine METOS WD-151E TOUCH R-L 400/3PE/50Hz Marine

Hot water flow l/min	11
Hot water min pressure kPa	100
Hot water max pressure kPa	600
Hot water conn. height mm	1395
Drain diameter	50
Drain flow l/s	3
Drain conn. inlet	Right;Behind;Bottom
Floor drain needed	Yes
Sound level dB	68
HACCP-connectivity	YES
Heat load sensitive W	4500
Heat load latent W	3000
Water consumption	cold water consumption, final rinse normal (litres/basket) 1.5