

Thaw cabinet Metos Pure CTPG1A 230/1PE/50Hz

MG4247515MT

Responsive humidity management. Automatic climate change management. 5" touch screen color display with control interface. Wide range of customization possibilities.

High efficiency tropicalized refrigeration unit. Model modularity. Monoblock construction. Internal stainless steel. External Scotch Brite satin finish stainless steel. Insulation thickness: 80 mm sides. 65 mm top. 60 mm external back and bottom.

High density CFC and HCFC-free PU insulation (42 kg/m3). Ergonomic handle. Self-closing doors with opening position block at 100° and magnetic gaskets on all 4 sides.

Easily-open Dashboard to facilitate periodic maintenance (condenser cleaning). Membrane control card with humidity regulation and HACCP alarms. Humidifier and air exchange system via an automatic extractor fan with controlled times. Monoblock ceiling system with an evaporator outside the cold room to allow for the exploitation of the entire refrigerated volume. Indirect ventilation thanks to the full-length duct system for optimal air circulation and uniform temperature distribution. Automatic defrosting and water condensation evaporation device . Tropicalized

group(class"T" 43°C). Rounded cell corners for easy cleaning. Locking fixtures. Climate class 5. Connectivity with remote control.

STANDARD EQUIPMENT:

- 4 "C"-SLIDES COUPLE
- 4 GN 2/1 GRIDS
- WI-FI CONNECTION
- CONNECTIVITY KIT

TEMP. -2 / +10 °C STORAGE - TEMP. -2 / +35°C THAWING - 510 LT - GN2/1 - AIR CONDENSING UNIT





Thaw cabinet Metos Pure CTPG1A 230/1PE/50Hz

Product capacity	13 X GN 2/1
Capacity	13 x GN 2/1
Inside measures mm	620x710x1442
Item width mm	780
Item depth mm	965
Item height mm	2090
Package volume	1.855
Unit of volume	m3
Package volume	1.855 m3
Package length	101
Package width	82
Package height	224
Package unit of dimension	cm
Package dimensions (LxWxH)	101x82x224 cm
Net weight	199
Net weight	199 kg
Gross weight	209
Package weight	209 kg
Unit of weight	kg
Connection power kW	1.998
Fuse Size A	10
Connection voltage V	230
Number of phases	1PE
Frequency Hz	50
Type of electrical connection	Plug
Type of the refrigerant	R290
Quantity of refrigerant g	115
Hinge location	right
GN size	2/1

Thaw cabinet Metos Pure CTPG1A 230/1PE/50Hz

Temperature area °C	-2°C - +35°C
Lighting	LED
Defrosting	automatic
Glass door	No