

Waste disposer Disperator

530A-BS-K 440/3PE/60

Marine

MG4000630MM

Waster disposer Metos Disperator BS-K Undersink model. Disperator food waste disposers are used in galleys and kitchens around the world. Stainless steel 304 exterior housing. Specially cast steel alloy grinding unit High protection class for electrical components Allows continous feeding of food waste CE compliance Complies to MARPOL regulation

Standard delivery includes:

- 1 pc contactor with motor protector
- 1 pc flushing nozzle
- 1 pc protection lid with safety interlock swicth
- 1 pc solenoid valve
- 1 pc line strainer
- 1 pc jam release wrench for grinding unit"



Waste disposer Disperator 530A-BS-K 440/3PE/60 Marine

Product capacity	700 kg/hour
Item width mm	310
Item depth mm	310
Item height mm	780
Package volume	0.101
Unit of volume	m3
Package volume	0.101 m3
Package length	37
Package width	37
Package height	74
Package unit of dimension	cm
Package dimensions (LxWxH)	37x37x74 cm
Net weight	42
Net weight	42 kg
Gross weight	47
Package weight	47 kg
Unit of weight	kg
Connection power kW	2.2
Fuse Size A	16
Connection voltage V	440
Number of phases	3PE
Frequency Hz	60
Protection rating (IP)	55
Type of electrical connection	Semifixed