

# Dryer Primus T35

## 440/3PE/60 Marine

**MG4160764MM**

Drum diameter Ø 930mm. Anthracite grey skinplate side and front

- standard stainless steel drum with large diameter
- easy-to-use microprocessor: Easy Control
- radial airflow with PowerDry® - maximal heat transfer
- low energy consumption
- short drying time
- large door opening (Ø80cm) for easy loading and unloading
- self cleaning lint screen
- capacity 35 kg

### OPTIONS

- reversing drum
- residual moisture control Sensodry®:
- safe drying of delicate linen
- humidity detection in %
- ideal in combination with SoftWash®
- ideal for dry cleaners, fire departments
- available on Full Control
- standard stainless steel drum with large diameter
- radial airflow with PowerDry® - maximal heat transfer
- large door opening (Ø80cm) for easy loading and unloading



## Dryer Primus T35 440/3PE/60 Marine

Product capacity	35 kg
Item width mm	965
Item depth mm	1490
Item height mm	1975
Package volume	3.323
Unit of volume	m3
Package volume	3.323 m3
Package length	104
Package width	154
Package height	207.5
Package unit of dimension	cm
Package dimensions (LxWxH)	104x154x207.5 cm
Net weight	305
Net weight	305 kg
Gross weight	330
Package weight	330 kg
Unit of weight	kg
Connection power kW	36
Connection voltage V	440
Number of phases	3PE
Frequency Hz	60
Protection rating (IP)	43
Type of electrical connection	Semifixed