



Information about electrical connection can be found on the dishwasher's wiring diagrams.

- ① Drain 50 mm. The drain pipe can be connected to the dishwasher drain or run to a floor drain, where it must end above the water level. The drain should be a metal pipe if there is a risk of mechanical collision.

| Code      | Electric supply  | P/kW |
|-----------|------------------|------|
| 4208126MK | 3PE AC 400V 60Hz | 0,12 |
| 4208126MM | 3PE AC 440V 60Hz | 0,12 |

|  |                    |   |                               |
|--|--------------------|---|-------------------------------|
| Vers.  | Muutos:            | Pvm.  | Suun.                         |
| Tämä piirustus on Metos Oy Ab:n omaisuutta, kopiointi tai osittainenkin jäljentäminen ilman Metos Oy Ab:n lupaa on ehdottomasti kielletty.<br>This document may not be copied in part or in whole by any process nor passed on to a third party without the written permission of the owner Metos Oy Ab. |                    |   |                               |
| Suun.  | Kaupalliset asiat: | Työmaa-asiat:   |                               |
| Suhde:   | 1: 15 A4           | Proj.no<br><a href="http://www.metos.com/">www.metos.com/</a> | Tarj./tilausno. Pvm. 5.4.2019 |
| <b>metos</b>   |                    | Nimitys<br>Motor-powered turn track WD-C 90° R-L              |                               |
| Metos Oy Ab<br>FI-04220 KERAVA<br>Tel: 0204 39 13 Fax: 0204 39 4432  |                    |   | Piir.no<br>Lehti              |