

Prewash shower Metos 6548 LEED wall mounted

MG4218497

Metos TOPCLEAN 6548 LEED Pre-Rinse Shower is made of acid-resistant 316L stainless steel, making it suitable even for demanding environments. The model meets the requirements set by the EU for water fixtures. Thanks to its new design, the spout is positioned above the dishwashing baskets rather than in front of them. The restricted flow of the spray head is designed to ensure effective pre-rinsing while reducing water consumption. The hand shower activates automatically when pulled downward and shuts off when released or when the handle is lifted. The shut-off mechanism is located before the hose, preventing pressure from remaining in the hose.

Standard delivery includes:

- Thermostatic mixer
- Spout, flow rate 19–27 l/min (2–4 bar)
- LEED hand shower, flow rate 6 l/min (2–4 bar)
- Upper wall support



Prewash shower Metos 6548 LEED wall mounted

Item width mm	272
Item depth mm	165+270
Item height mm	1050
Package volume	0.22
Unit of volume	m3
Package volume	0.22 m3
Package length	50
Package width	40
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	50x40x110 cm
Net weight	10
Net weight	10 kg
Gross weight	11
Package weight	11 kg
Unit of weight	kg
Cold water diam.	G1/2"
Cold water min pressure kPa	100
Cold water max pressure kPa	600
Hot water diam.	G1/2"
Hot water min pressure kPa	100
Hot water max pressure kPa	600
Remarks (hot water)	max. +80°C
Mixer type	2 handles