

Combi kettle Metos Proveno Combi 300S



Product information

SKU 4222057

Product name Combi kettle Metos Proveno Combi 300S

Dimensions $1550 \times 1160 \times 1280 \text{ mm}$

Weight 534,000 kg

Capacity 300 L

Technical information 400/230 V, 16 A, 2 kW, 3NPE, 50 Hz CW: 15

HW: 15

Description

• direct steam combi kettle with a mixer. Intelligent TempGuard-temperature control includes following functions: food temperature (food must be mixed for even temperatures), Proving Control. BurnPrevent Control,

Automatic ½-energy

- liftoff hinged s/s lid is heavy-duty and dishwasher proof, fully isolated kettle part, automatic filling of steam generator
- CSFP-customer parameters: make your owns settings and Proveno works for just for you!
- material throughout stainless steel, inner surface acid proof stainless steel (EN 1.4432)
- temperature range 0 120 °C (max. working pressure 1, 0 bar)
- mixer with autoreverse and preset mixing programmes tested by chefs
- mixing speed 15-140 rpm (all sizes), power mixing function
- service free mixer (sealing always above food level), mixing tool with always clean handle for easy lifting after production
- Standard equipment: support pillar, measuring stick, liftoff closed lid, mixing tool with removable scrapers (dishwasher proof)
- Options for surcharge: liftoff safety grid for lid, manual cooling, hand shower, control pillar cover tray, installation frames, s

trainer plate, pouring adapter (150-300 l), TempNet -program for HACCP, draw off tap

Metos Marine marine, metos, com 1/2

