

## Combi kettle Metos Proveno Cool 60S



## **Product information**

SKU 4222080

Product name Combi kettle Metos Proveno Cool 60S

Dimensions  $1037 \times 620 \times 1280 \text{ mm}$ 

Weight 204,000 kg

Capacity 60 L

Technical information 230 V, 16 A, 1 kW, 1NPE, 50 Hz CW: 15 HW: 15

## **Description**

- direct steam combi kettle with a mixer. Intelligent TempGuard-temperature control includes following functions: food temperature (
  - food must be mixed for even temperatures), Proving Control. BurnPrevent Control, Automatic ½-energy
- liftoff hinged s/s lid is heavy-duty and dishwasher proof, fully isolated kettle part, automatic filling of steam generator
- CSFP-customer parameters: make your owns settings and Proveno works for just for you!
- material throughout stainless steel, inner surface acid proof stainless steel (EN 1.4432)
- temperature range 0 120 °C (max. working pressure 1, 0 bar)
- mixer with autoreverse and preset mixing programmes tested by chefs
- mixing speed 15-140 rpm (all sizes), power mixing function
- service free mixer (sealing always above food level), mixing tool with always clean handle for easy lifting after production

Standard equipment: automatic cooling, liftoff lid with liftoff safety grid, hand shower, control pillar cover tray, support pillar,

measuring stick, mixing tool with removable scrapers (dishwasher proof)

Options for surcharge: Icewater cooling connections (C3), Two-phase cooling connections (C5), installation frames, strainer plate, p

ouring adapter (150-300 I), TempNet -program for HACCP, draw off tap

Metos Marine marine, metos, com 1/2

