

OVEN Oven group Chef240/240/200/2908 -440V3~ MAR



Product information

SKU Product name

Dimensions Weight Capacity Technical information 3752953 OVEN Oven group Chef240/240/200/2908 -440V3~ MAR 800 × 800 × 1620 mm 185,000 kg 2x uuni 2xGN2/1 + 4xGN2/1 440 V, 25 A, 16,1 kW, 3PE, 50/60 Hz CW: 3/4" Drain: ø 16 mm

Description

Oven group for marine use with 2 Chef 240 convection ovens 1 Chef 200 proving cabinet mounted on stand Chef 2908.

CHEF 240 CONVECTION OVEN

- cooking cabinet, door and external surfaces stainless steel
- temperature: +50-300°C
- timer 0-120 min or continuous
- manual valve for taking out the humidity from the cabinet
- oven cabinet with drain
- manual humidification, also with continuous humidification: when requested, humidification level can be changed



- 2 removable pairs of rails for 2 x GN2/1 Optional extras:
- 3 pairs of rails for baking (bake-off)

CHEF 200 PROVING CABINET

- cabinet, door and external surface stainless steel
- temperature: +20-60°C
- timer 0-120 min or continuous
- pre-heating time (35°C): 20 min
- humidity % can be adjusted
- water pool filling by turning switch Optional extras:
- rack for baking trays: 5 pairs of rails, 450x600 mm