

Circulator bath Metos Fusion Diamond M 230V1~



Product information

SKU 4163618

Product name Circulator bath Metos Fusion Diamond M

230V1~

Dimensions $332 \times 577 \times 424 \text{ mm}$

Weight 15,000 kg Capacity 27 I water bath

Technical information 230 V, 10 A, 2,0 kW, 1N, 50 Hz

Description

- circulator is mounted on a bridge over the bath
- VFD -display, resolution ± 0.01 °C
- safety protection grid prevents the vacuum pouch from touching moving and heated parts.
- circulating pump ensures optimal temperature stability and water distribution throughout the bath
- 3 integrated timers allows for easy monitoring of the elapsed or remaining cooking time.
- pre-programmed memory keys for 3 different types of foods
- easy HACCP data logging
- Smudge-Proof Stainless Steel Hood
- Low-Level Water Alarm
- Vapor Barrier Protection
- Core Temperature Detection (audible and visual)
- Intuitive Automatic Calibration
- Simultaneous Display of Setpoint, Current Temperature, Core Temperature/Timer
- PC Controlled

Metos Marine <u>marine.metos.com</u> 1/2



Accessories (not included in the price):

- separation grids
- core temp sensor Pt100
- sous-vide neopreeni -tape
- HACCP software
- PC -cables, USB or RS232