

Dishwasher Metos WD-6+DD 440/3PE/60 Marine



Product information

SKU 4246077

Product name Dishwasher Metos WD-6+DD 440/3PE/60 Marine

Dimensions $600/695 \times 657/700 \times 1430/1880 \text{ mm}$

Weight 93,000 kg

Technical information 440 V, 9,75 kW, 3PE, 60 Hz HW: 1/2" Drain: ø 50

mm

Description

- hoodtype of dishwasher
- · noise and heat insulated
- electronic control
- three washing cycles. Possibility to programme washing and rinsing times as well as rinsing temperatures. This makes it possible to have e.g. an own programme for fine porcelain having a lower rinse temperature
- hygiene warranty: machine indicates too low temperatures and continues washing if rinsing temperature is too low
- good rinsing result is always secured: machine controls the rinse water flow and it indicates too low a flow to the user
- easy to use: machine warns of a closed tap and of a misplaced overflow tube
- digital control panel shows the daily and total amount of washed racks: it also displays the programme, temperatures and washing time remaining

Metos Marine marine.metos.com 1/2



- easy to keep clean: automatical cleaning programme
- unique hood prevents the steam from evacuating against the face of the user when the hood is opened
- wash arm empties it self from washing water when rinsing starts, this quarantees a sparkling rinsing result
- · washing arms are self cleaning
- rack size 500 x 500 mm
- · washing cycle starts when the hood is closed
- tank volume 50 l Standard equipment:
- rinse aid dispenser
- plate rack
- cup rack
- utensil rack
- detergent dispenser for liquid detergent Extra equipment:
- water connection pipe with stop cock, non-return and vacuum valves
- steam hood which is connected to the machine: steam is released to the ventilation channel instead of the dishwashing room
- machine with a booster pump
- machine with a drain pump
- · cold water connected machine
- · automatic control of the ventilation fan