

Ice maker Metos C46 AX AG with filter 220/1PE/60 Marine



Product information

SKU 4173191ME

Product name Ice maker Metos C46 AX AG with filter

220/1PE/60 Marine

Dimensions $500 \times 540 \times 690/774 \text{ mm}$

Weight 38,000 kg

Capacity production 46kg/24h,bin 15kg

Technical information 230 V, 10 A, 0,480 kW, 1PE, 60 Hz CW: 3/4"

Drain: øØ 20

Type of the refrigerant R290 Quantity of refrigerant 70

[g]

Cooling capacity [W] 1054

Description

The Metos C-series ice makers are efficient ice cube makers with their own ice container. The compact dimensions of the machines make them suitable for small spaces, as well as allows them to be installed below a surface. The machines produce clear, transparent ice cubes that help the drink stay cool longer. This is why the C-series' ice machines are perfect for bars, cafes, small restaurants and kiosks.

Special attention has been paid to the hygiene and ease of use in the

Metos Marine marine.metos.com 1/2



design of the machines. The machines have an automatic washing system that ensures easy cleaning. The internal cleaning and maintenance of the machine is also effortless due to easy access. The frame of the machine is made of wear-resistant and easy-to-clean stainless steel. The controls of the machines work electronically, which allows the detection of malfunctions and can be used to determine the efficiency of the machine.

- air condensation
- filter
- clear and transparent ice cubes that help the drink stay cold longer
- ice cube size 20 g
- water is sprayed into the evaporator
- integrated ice container with door
- · stainless steel body
- automatic washing system
- environmentally friendly R290 as refrigerant

DELIVERY INCLUDES:

- ice bucket
- pressure water hose
- drain hose
- adjustable feet Ø50mm H100-120 mm

FACTORY OPTIONS (to be ordered with the machine):

- ozone programmable sanitation cycle
- Rainbow technology evaporator treatment
- IOT cloud connection
- programmable ice production
- drain pump

The capacity values have been calculated under conditions where the room temperature is 10° C and the water temperature is 10° C. If the water used is warmer, the output of the machine will decrease.