

Thaw cabinet Pure Metos 230/1PE/50Hz CTPG1A



Product information

SKU	4247515MT
Product name	Thaw cabinet Pure Metos 230/1PE/50Hz CTPG1A
Dimensions	780 × 965 × 2090 mm
Weight	199,000 kg
Capacity	13 X GN 2/1
Technical information	230 V, 10 A, 1,998 kW, 1PE, 50 Hz
Type of the refrigerant	R290
Quantity of refrigerant [g]	115

Description

Responsive humidity management. Automatic climate change management. 5" touch screen color display with control interface. Wide range of customization possibilities.

High efficiency tropicalized refrigeration unit. Model modularity. Monoblock construction. Internal stainless steel. External Scotch Brite satin finish stainless steel. Insulation thickness: 80 mm sides, 65 mm top, 60 mm external back and bottom.

High density CFC and HCFC-free PU insulation (42 kg/m³). Ergonomic handle. Self-closing doors with opening position block at 100° and magnetic gaskets on all 4 sides.

Easily-open Dashboard to facilitate periodic maintenance (condenser cleaning). Membrane control card with humidity regulation and HACCP alarms.

Humidifier and air exchange system via an automatic extractor fan with controlled times. Monoblock ceiling system with an evaporator outside the cold room to allow for the exploitation of the entire refrigerated volume.

Indirect ventilation thanks to the full-length duct system for optimal air circulation and uniform temperature distribution. Automatic defrosting and water condensation evaporation device . Tropicalized group(class“T” 43°C). Rounded cell corners for easy cleaning.

Locking fixtures. Climate class 5. Connectivity with remote control.

STANDARD EQUIPMENT:

- 4 "C"-SLIDES COUPLE
- 4 GN 2/1 GRIDS
- WI-FI CONNECTION
- CONNECTIVITY KIT

TEMP. -2 / +10 °C STORAGE - TEMP. -2 / +35°C

THAWING - 510 LT - GN2/1 - AIR CONDENSING UNIT